



KINGFISHER ALKYD PRIMER UNDERCOAT

DESCRIPTION.

Kingfisher Alkyd Primer Undercoat is a 60% solids leadless primer suitable for the protection of woodwork under interior or exterior conditions.

It dries to an eggshell finish and can be over coated with all conventional oxidisable systems such as undercoats and finishes..

PREPARATION.

All wood surfaces should be clean and free from grease and dust.

APPLICATION

It is recommended that the product be applied by brush but it can also be applied by spray.

COVERAGE.

The covering capacity of **Kingfisher Alkyd Primer Undercoat** will vary dependent upon the nature and porosity of the surface it is being applied to.

Approximate figures (for guidance only) would be 8 sq. metres per litre for open grain softwoods to 14 sq. metres per litre for close grain hardwoods.

<u>Drying Time @ 20 °C.</u>	Surface Dry	-	5 – 6 hours.
	Hard Dry	-	16 hours
	Overcoating	-	16 hours.

PACKAGING.

Kingfisher Alkyd Primer Undercoat is available in 5 litre tins.

COLOUR. White.

HEALTH & SAFETY PRECAUTIONS

Toxicity

The solvent vapour from the product is not very high but inhaling the concentrated vapours for any length of time can result in dizziness or nausea. These effects should be temporary.

Fire Risk.

The solvent vapour is inflammable and no naked lights or sources of ignition should be allowed in the vicinity during its use.

SMOKING SHOULD BE PROHIBITED WHEN USING THIS PRODUCT

For further Health and Safety information on this product please refer to the Kingfisher Safety Data Sheet, copies of which are available from the Kingfisher Technical Dept. Tel. 01229 869100 or Fax 01229 868101.