



EXTREME CLIMATE

DESCRIPTION.

Kingfisher EXTREME CLIMATE is the very latest development in penetrating damp prevention.

Using the latest solvent based fluorochemical resin technology Kingfisher has developed a product which imparts oil and water repellence to stone, ceramic and concrete surfaces. Extreme Climate will not change the colour of the material to which it is applied and due to its molecular structure will also keep the surface clean and free from general dirt and grime.

APPLICATION

It is very important that the surface to be treated is dry and masonry joints are sound, free from cracks and that all debris is removed before application.

The product is supplied ready to use and can be applied to the substrate by spray, brush or roller.

DRYING.

Allow to dry for approximately 12 hours. In case of light precipitation the surface should be covered until dry.

COVERAGE.

Dependent on the porosity of the surface 1 litre of product should cover approximately 3-5 m².

STORAGE / SHELF LIFE.

Shelf life of *Kingfisher EXTREME CLIMATE* is approximately 24 months from date of manufacture.

DO NOT store at temperatures above 40°C.

KEEP AWAY from sparks, open flames and other sources of ignition.

Keep container tightly closed when not in use.

HEALTH & SAFETY PRECAUTIONS.

Use only in well ventilated areas.

Keep out of reach of children.

This product is designated HARMFUL and may cause lung damage if swallowed.

In case of contact with eyes and skin rinse the affected areas immediately with plenty of water.

For further Health and Safety information on this product please refer to the Kingfisher Safety Data Sheet, copies of which are available from the Kingfisher Technical Dept. Tel. 01229 869100 or Fax 01229 868101.