

GEOFIX PAVING JOINTING COMPOUND

DESCRIPTION

GEOFIX PAVING JOINTING COMPOUND is a unique ready to use self curing jointing material for all types of paving having joints of 5mm and over. GEOFIX PAVING JOINTING COMPOUND is a quick and easy way of applying a permanent rigid joint with no special machinery or equipment required. GEOFIX PAVING JOINTING COMPOUND is suitable for natural stone, concrete, slate, clay, terracotta and granite and can be used in areas subject to light vehicular traffic.

BENEFITS

- * Supplied ready to use, no mixing required.
- * Simply brush into joints and compact.
- * Cement free – Non staining.
- * Sets hard, wont crack or wash out.
- * Resists weeds and plant growth.
- * Totally weatherproof, unaffected by frost.
- * For all joints of 5mm wide and over.
- * Water permeable, allows water to escape.

AREAS FOR USE

- * Footpaths.
- * Outdoor patio areas.
- * Indoor stone floor areas.
- * Pedestrian areas.
- * Driveways.

LIMITATIONS

- Do not use on joints smaller than 5mm.
- Joint depth must be a minimum of 25mm
- Do not apply to wet areas or when rain is imminent or below 0⁰C
- In areas subject to vehicular traffic it is essential that the paving elements are bedded on a class 1 mortar and a high percentage of the mortar is squeezed up the joint, thereby providing support for the paving elements.
- GEOFIX should be considered for its aesthetic and not its structural properties.
- The jointing should not be cleaned by use of high pressure washers until cured for 7 days. The distance between nozzles to jointing must be at least 10cm.

- Always follow the manufacturer's instructions carefully. As the company cannot be aware of all the applications and materials the product may be used on, it is the users responsibility to determine suitability for use. Please contact technical services for advice or request technical data sheet.

SURFACE PREPARATION

Ensure that the paving to be jointed is dry and free from loose dirt, oil, debris and grease etc. it is essential the joint widths are a **minimum** of 5mm wide with a **minimum** depth of 25mm. deeper joints can be filled with dry sand or other materials to meet the required minimum depth.

APPLICATION

GEOFIX is supplied ready to use and does not require any further mixing or addition of other materials.

Carefully open the vacuum packed bag and sprinkle GEOFIX PAVING JOINTING COMPOUND sufficient to cover an area of 4-5m² (see coverage table below). Using a soft brush, push the GEOFIX PAVING JOINTING COMPOUND into the joints ensuring they are filled with the material.

Protect treated joints from rain until fully cured. Any contact with rain and water before the compound has set will affect the product.

To ensure a perfect joint, press the GEOFIX PAVING JOINTING COMPOUND into the joints with a pointing tool or compact into joints using a vibrating plate. Top up as necessary.

Any residue left on the surface when cured can be simply cleaned off by sweeping with a stiff brush.
Kg/m²

COVERAGE (the figures given below are approximate quantities required)

	5mm Joint Width, 25mm depth	10mm joint width, 25mm depth
Mosaic 60mm x60mm	6.5-7.5 Kg/m ²	13.5-14.5 Kg/m ²
Small 100mm x 100mm	3.75-4.25 Kg/m ²	7.5-8.5 Kg/m ²
Large 400mm x 400mm	1-1.5 Kg/m ²	2-2.12 Kg/m ²

SPECIFIC DATA

Material	Ready to use sand mixture with Polybutadiene bonding agent.
Density (approx)	1.70 g/cm ³
Colour	Beige/grey
Storage	Cool dry conditions away from direct sunlight
Packaging	9kg and 20kg hermitically sealed vacuum packed foil bags.
Joint width	Minimum 5mm
Min joint depth with foot traffic	Minimum 25mm
Min joint depth with light vehicular traffic	Minimum 40mm
Working temperature	0 to +40 degrees C
Workability duration	Approx 45 minutes @ 23 degrees C. Higher temperatures reduce working time.

Compressive Strength (Nmm²)

	Sand Cement Mortar	GEOFIX
1 day	4	6
7 days	8	12
28 days	13	18

Flexural Strength (Nmm²)

	Sand Cement Mortar	GEOFIX
1 day	5	6
7 days	11	14
28 days	13	15

HEALTH AND SAFETY

For full information on Health and Safety regarding this product, the relevant health and safety data sheet should be consulted.

STORAGE

Store in a cool dry place. Protect packaging from punctures or piercings. Any exposure to air will start the curing process. Do not store in direct sunlight.

SHELF LIFE

TECHNICAL DATA SHEET NO: GEOFIX
PAGE: 4 of 4

VERSION: 1/12/12/2008
PRINT DATE: 9/14/2009

24 months from date of manufacture when stored in unopened containers in accordance with manufacturer's instructions.