



K - BOND

DESCRIPTION.

Kingfisher K-BOND is a specialised PVA bonding agent designed specifically for cement and gypsum based bonding situations which conforms to BS5270.

Kingfisher K-BOND will give improved adhesion to all cement and gypsum renders or plasters, aid the bond strength for concrete repairs and stabilise friable substrate. Further **K-BOND** will reduce the suction of a background when applied to the substrate and will improve the bonding capability when used as an admixture.

METHOD of USE.

Use **Kingfisher K-BOND** as an admixture, diluted with water to improve the workability and adhesion of the mix. For stronger bonds use a more concentrated solution. Used as a primer, mix with cement and render onto surface whilst tacky.

APPLICATION.

Dilute 1:3, 1:2, or 1:1, with water, depending on the strength of bond required when using as an admixture

To use as a dustproofer on concrete surfaces or to stabilise a substrate prior to painting or rendering dilute to a 1 : 2 ratio with water.

Use a 1 : 1 **K-BOND** to water ratio, mixed with neat cement to a slurry as a bonding primer onto difficult surfaces.

PACKAGING.

5 Litre and 25 Litre Plastic containers.

Protect from frost.

HEALTH and SAFETY.

Avoid repeated contact with skin and eyes. In cases of eye contact rinse with copious amounts of clean water.

NOTE: - THIS MATERIAL CANNOT BE USED AS A WOOD ADHESIVE.

Further Health and Safety information on this product is provided in the MSDS, copies of which may be obtained from the Kingfisher Technical Dept. Tel 01229 869100 or Fax 01229 869101.