



## **K-GRIP ADVANCED ADHESIVE**

### **DESCRIPTION.**

**Kingfisher K-GRIP** is a direct bond adhesive with superior non-slump qualities. Formulated with state of the art resin technology. Direct bond is achieved in most cases without the need of temporary support.

### **ADVANTAGES.**

- No stringing in use.
- Excellent cut off properties.
- Superior slump resistance ensures instant bond to most common substrates without the use of temporary support in most cases.
- Improved early adhesive strength.
- Internal and External use.
- Can be over painted.

### **AREAS FOR USE**

**Kingfisher K-GRIP** is a one-part adhesive, developing a high bond strength, formulated to bond a wide range of materials, such as Skirting, Timber Battens, block board, hardwoods, plywood's, chipboard, rigid plastics, PVCu, (excluding polystyrene materials), aluminium, steel, galvanised steel sheeting, to either themselves or to block work, brick, stone, cement based renders or screeds, plaster and plasterboard insulation boards.

### **APPLICATION**

Cut off cartridge tip above screw thread. Screw nozzle onto cartridge tip and cut nozzle end at a 45° angle and to required bead width.

Insert cartridge into sealant gun and squeeze trigger to apply.

### **LIGHTWEIGHT ITEMS.**

Apply minimum 6mm x 6mm zigzag bead of **Kingfisher K-GRIP** across the bonding surface. Press firmly into place (with twisting action if possible) and apply even pressure to seat to substrate. Remove excess adhesive before curing has taken place.

### **HEAVY or IMPERVIOUS ITEMS or Thin Boards to uneven surfaces.**

Apply as for lightweight items.

**Note.** Extremely heavy unsupported items may need temporary support for up to 24 hours.

### **CARPET GRIPPERS, STAIR NOSINGS etc.**

Apply a continuous 6mm x 6mm bead to the bonding surfaces. If possible, slide into place with even pressure. Vertically applied heavy wall edge protectors may need temporary support. Allow product to fully cure before allowing heavy foot traffic.

### **EXTERNAL APPLICATIONS.**

When used externally the adhesive bond line of **Kingfisher K-GRIP** must be protected from driving rain and permanently wet or ponded areas

### **PACKAGING**

**Kingfisher K-GRIP** is available in 310 ml rigid cartridges. Standard box quantities. 12.

### **STORAGE / SHELF LIFE.**

The shelf life of **K-GRIP** is 12 months when kept in unopened cartridge and stored at a temperature of +5 to +25°C. and out of direct sunlight.

Store on tightly closed containers in accordance with the Highly Flammable Liquids Liquefied Petroleum Gases Regulations (1972).

### **HEALTH and SAFETY.**

This product is classified as Flammable and should be kept away from sources of ignition.

Electrical power tools, light and power switches may generate sparks sufficient to ignite the product or its vapour.

Avoid skin and eye contact. In the event of contact with the eyes, rinse with copious amounts of clean water for 15 minutes. Seek medical attention.

Keep out of reach of children.

Use only in well ventilated areas

For further Health and Safety information on this product please refer to the Kingfisher Safety Data Sheet, copies of which are available from the Kingfisher Technical Dept. Tel. 01229 869100 or Fax 01229 869101.

THE INFORMATION GIVEN IN THIS DATA SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS TO THE BEST OF THE COMPANY'S KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS OF THE DATE INDICATED. HOWEVER NO WARRANTY, GUARANTEE OR REPRESENTATION IS MADE AS TO IT'S ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY THEMSELVES AS TO THE SUITABILITY AND APPLICATION OF SUCH INFORMATION FOR THEIR OWN USE.