



KOLOURSEAL (Roof Renovation)

DESCRIPTION.

Kingfisher Kolourseal. is an advanced acrylic polymer coating system specifically designed to completely renovate and transform roof and wall surfaces. Using new advanced micro polymer technology Kingfisher have produced a highly durable product which not only seals porous roof tiles but transforms and enhances the appearance of the property.

The **Kingfisher Kolourseal** coating system is micro porous, allowing moisture vapour to pass through the film from the roof substrate to the atmosphere while remaining impervious to mass water penetration.

This permeability function prevents blistering, delamination and premature adhesion failure when the system is installed correctly. **Kolourseal** is also UV light resistant and thus combats the sun's fading action, helping the coating to retain its colour over long periods.

PREPARATION.

The roof / wall being treated should be cleared of debris, algae, moss lichen and other accumulated dirt and then pressure washed off.

It is also recommended that ridges and verges be repointed and broken and loose tiles replaced or repaired prior to treatment.

Stubborn contaminates should be removed by scrubbing with a wire brush before proceeding further.

*After cleaning, the roof / wall should be allowed to dry. **Kingfisher Biocidal Wash** diluted 3:1 with water is then applied as a sanitising agent to kill all traces of moss and algae spores.

Note: **This is a critical stage in the application process and must be carried out to ensure correct adhesion and system longevity.*

Kolourseal can now be applied to the prepared surfaces.

APPLICATION

To obtain the most effective results from **Kingfisher Kolourseal** it is preferred that the product be applied by brush, roller or high pressure spray.

COVERAGE.

Kingfisher Kolourseal will cover approximately 4-6 sq metres per litre depending upon the porosity of the surface it is being applied to.

PACKAGING /COLOURS.

Kingfisher Kolourseal is supplied in 20 kg plastic buckets and is available in a variety of colours, including.....

- Stoker Grey ● Mid Grey ● Terracotta Clay ● Brown ● Black Anthracite ●
- Spanish Terracotta. ● Dark Terracotta. ● Green. ●

The product is non hazardous in normal use.

For further Health and Safety information on this product please refer to the Kingfisher Safety Data Sheet, copies of which are available from the Kingfisher Technical Dept Tel. 01229 869100 or Fax 01229 869101.
www.kingfisheruk.com

THE INFORMATION GIVEN IN THIS DATA SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY PROCESS. SUCH INFORMATION IS TO THE BEST OF THE COMPANY'S KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS OF THE DATE INDICATED. HOWEVER NO WARRANTY, GUARANTEE OR REPRESENTATION IS MADE AS TO IT'S ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USERS RESPONSIBILITY TO SATISFY THEMSELVES AS TO THE SUITABILITY AND APPLICATION OF SUCH INFORMATION FOR THEIR OWN USE.