



KINGFISHER WATERPROOFER

DESCRIPTION.

Kingfisher WATERPROOFER is a concentrated admixture for render, mortar and concrete. It inhibits passage of water and salts from the wall whilst allowing the wall to breathe, ensuring normal evaporative drying. **Kingfisher WATERPROOFER** acts as a plasticiser on use as instructed.

Kingfisher WATERPROOFER provides benefits in backing render coats by reducing suction and ensuring efficient and firm bonding of pebble dash into final render coats.

Kingfisher WATERPROOFER can be used in mortar for engineering brick in below ground situations e.g. Manhole and septic tank chambers.

METHOD of USE.

Kingfisher WATERPROOFER is a viscous alkaline red liquid concentrate and should be diluted to the ratio of 1 part Waterproofer to 30 parts water as gauging for end use.

Coverage: 0.5 litres / 50kgs cement.

Approx.: 0.05 litres per sq. metre render at 10mm thickness.

HEALTH and SAFETY.

This product is alkaline and contact with eyes and skin should be avoided.

Keep away from children and animals.

Kingfisher WATERPROOFER is water based concentrate and should be protected from frost.

For further Health and Safety information on this product please refer to the MSDS, copies of which can be obtained from the Kingfisher Technical Dept. Tel 01229 869000 or Fax 01229 869101.