

MATERIAL SAFETY DATA SHEET



Drywall Renovating Plaster

Issue: 2. Issue Date: 08/08/2006.

Page 1 of 4

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY

Product Name. Kingfisher Drywall Renovating Plaster

Supplier. KINGFISHER BUILDING PRODUCTS Ltd.
COOPER LANE.
BARDSEA BUSINESS PARK
ULVERSTON
CUMBRIA.
LA12 9RA.

Telephone: 01229 869100
Fax: 01229 869101
Emergency: As Above

2. COMPOSITION / INFORMATION ON INGREDIENTS.

Ingredient Name.	CAS.No	Einecs	Content	Health (Class)	Risk (R No.)
Blend of O.P.C, lime & pearlite Lightweight aggregate.	1305-62-0	125-137-3	100%	Xi .	R38

3. HAZARDS IDENTIFICATION

FIRE: - Non flammable

ENVIRONMENT: -

HEALTH Irritant to skin and eyes.

Inhalation: - Irritant to mucous membrane and upper respiratory tract.

Eye Contact: - Mild exposure may cause soreness. Gross exposure can lead to chemical burning and ulceration.

Skin Contact: - May cause irritation to th skin.

4. FIRST AID MEASURES.

Inhalation:- Remove patient to fresh air. If patient is unconscious place in recovery position. Seek immediate medical attention

Eye Contact: - Wash eyes with water or saline solution for at least 15 minutes. Seek medical advice.

Skin Contact: - Wash thoroughly with plenty of running water. If irritation persists seek medical advice.

Ingestion:- Wash mouth with plenty of water. DO NOT induce vomiting. In case of spontaneous vomiting ensure vomit can drain freely to avoid suffocation. Seek medical attention.

MATERIAL SAFETY DATA SHEET (Continued)

Drywall Renovating Plaster.

Issue No: 2. Issue Date: 08/08/2006

Page 2 of 4

5. FIRE FIGHTING MEASURES.

Extinguishing Media:- None required non flammable product.

Protective Measures in Fire:- Use extinguisher relative to surrounding fire conditions.

6. ACCIDENTAL RELEASE MEASURES.

Personal Protection during Spill:- Wear suitable protective clothing and eye / face protection

Precautions to Protect Environment:- Recover spillage in dry state if possible.

Spillage Clean Up Methods:- Take up material. Avoid air borne dust. Place in enclosed containers. Dispose as waste. May be slurried with water.

7. HANDLING AND STORAGE.

Usage Precautions:- Ensure adequate ventilation. Avoid creation of dust. Wear suitable PPE i.e. mask, goggles and protective overalls. Do not breathe dust. Avoid eye contact.

Storage Criteria:- Keep in original container. Keep dry. Bags should be stacked in safe and stable manner.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION.

INGREDIENT.	CAS. No.	STD OEL (8hr.TWA)	LT EXP (8 Hrs)	ST EXP (15 Min)
Respirable Dust		5mg/m ³		

Personal Protective Equipment:- Wear gloves, safety glasses, overalls and closed footwear.

Hygienic Work Routines:- Wash hands thoroughly before eating, drinking or smoking.

MATERIAL SAFETY DATA SHEET (Continued)

Drywall Renovating Plaster.

Issue No: 2. Issue Date: 08/08/2006

Page 3 of 4

9. PHYSICAL AND CHEMICAL PROPERTIES.

Appearance: - Powder.	Colour:- Grey
Odour: - Non discernable.	Viscosity:- N/A
Solubility in Water: - Insoluble.	Flash Point: - N/A
Boiling Point: - N/A.	Density: - N/K.
Vapour Pressure mm Hg @ 20°C: - N/A	Lower Explosion Limit: - N/A
Specific Gravity: - N/A	pH value: - N/K.

10. STABILITY AND REACTIVITY

Stability: Stable in normal storage conditions. Soluble in acids. Insoluble in methanol and acetone

Materials to Avoid: Non known

Conditions to avoid: Non known

11. TOXICOLOGICAL INFORMATION.

Inhalation: Causes respiratory irritation.

Skin Contact: May cause irritation to the skin. Prolonged contact may cause dermatitis and/or burns.

Eye Contact: Can cause burns. Cement and lime components are severe eye irritants.

Ingestion: Causes irritation of the mouth, throat and respiratory tract.

Other: When mixed with water alkali is released. Precautions should be to prevent dry materials entering the eyes, mouth, nose and to prevent skin contact with wet mixed material.

12. ECOLOGICAL INFORMATION.

Environmental Hazards. Slightly toxic to birds.

Mobility; Granular powder,

Solubility: Forms aqueous mixture

13. DISPOSAL CONSIDERATIONS

Disposal Methods:

For large quantities, disposal must be carried out under guidance from local and national legislation. Small quantities can be disposed of as common waste via a waste contractor.

MATERIAL SAFETY DATA SHEET (Continued)

Drywall Renovating Plaster.

Issue No: 2. Issue Date: 08/08/2006

Page 4 of 4

14. TRANSPORT INFORMATION

Label for Conveyance. Not classified as dangerous for transportation.

Hazard Class.

UN No.

E.M.S.

I.M.D.G.

ICAO/ IATA.

Flashpoint.

Trans. Cat.

Marine Pollutant.

E.E.C. Number.

A.D.R.

Packaging Number.

15. REGULATORY INFORMATION

Label for Supply:



Xi Irritant

Contains Portland Cement and Lime.

Risk Phrases

R6/37/38

Irritating to eyes, respiratory system and skin.

Safety Phrases

S1/2.

Keep locked up and out of reach of children

S22.

Do not breathe dust.

S24/25.

Avoid contact with skin and eyes.

S26

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S28

After contact with skin wash with plenty of water.

S37/39

Wear suitable gloves and eye/face protection.

16. OTHER INFORMATION

User Notes :

THE INFORMATION GIVEN IN THIS DATA SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS TO THE BEST OF THE COMPANY'S KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS OF THE DATE INDICATED. HOWEVER NO WARRANTY, GUARANTEE OR REPRESENTATION IS MADE AS TO ITS ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY THEMSELVES AS TO THE SUITABILITY AND APPLICATION OF SUCH INFORMATION FOR THEIR OWN USE