



SAFETY DATA SHEET

FIBRESEAL

1. IDENTIFICATION OF SUBSTANCE/PREPARATION AND THE COMPANY..

PRODUCT NAME: FIBRESEAL

PRODUCT CODE: 70.

SUPPLIER: Kingfisher Building Products Limited.
Ulverston
Cumbria. LA12 9RA

www.kingfisheruk.com

Tel: 01229 869100
Fax: 01229 869101
E-mail: office@kingfisheruk.com
Emergency telephone. 01229 869100 0800 – 1700hrs. Monday to Friday only

2. HAZARDS IDENTIFICATION

Flammable; Harmful if swallowed; repeated exposure may cause skin dryness or cracking.
Harmful to aquatic organisms; may cause long term damage to the environment.

3. COMPOSITION / INFORMATION ON INGREDIENTS

A solvent based resinous roof coating.

| Hazardous ingredients: | Content Weight % | CAS No. | Hazard Symbol & Risk No. |
|-------------------------|---------------------|------------|----------------------------|
| Cynolac 60W | <40 | | R10, N:R51/53 |
| Xylene | <1 | 1330-20-7 | R10, Xn:R20/21,38. |
| White Spirit | <10 | 64742-82-1 | R10, Xn:R65,66, N: R51/53. |
| Plexigum Solution | <30 | | R10, Xi:R36,43. |
| Methoxy propyl acetate. | <10 | | R10 Xi:R36 |

4. FIRST AID MEASURES .

Skin contact: In case of contact with skin, wash immediately with plenty of soap and water.(S28) Do NOT use solvents to clean skin. If irritation persists seek medical attention

Eye Contact: In case of eye contact, rinse immediately with plenty of water and seek medical advice (S26).

Ingestion: If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

Inhalation: Remove to fresh air, keep patient warm and at rest. Persons who have inhaled substances may not exhibit symptoms immediately.

5. FIRE FIGHTING MEASURES

| | |
|------------------------------|---|
| Extinguishing Media: | In case of fire use water spray or fog, alcohol resistance foam, dry chemical or carbon dioxide (S43) |
| Exposure hazards: | In case of fires, do not breathe fumes |
| Protective equipment: | Fire fighters should wear self contained breathing apparatus and protective clothing to prevent skin contact. Do NOT allow run off from fire fighting to enter drains or water courses. |

6. ACCIDENTAL RELEASE MEASURES

| | |
|-----------------------------------|--|
| Personal precautions: | Exclude sources of ignition and ventilate area. Avoid breathing vapours. Refer to section 8 of the MSDS for personal protection details. |
| Environmental precautions: | Do not allow entry to drains or water courses. Contain the spillage. Should spillage enter drains or sewers, inform water authority/ environment agency immediately. |
| Clean up methods: | Absorb spillage in suitable inert material. Sweep or shovel up and transfer to closable, labeled container for appropriate disposal. |

7. HANDLING AND STORAGE

| | |
|-------------------------------|---|
| Handling requirements: | Do not breathe vapours / fumes (S23) Ensure there is sufficient ventilation of the work area (S51). Avoid contact with skin and eyes. Keep away from heat and sources of ignition. |
| Storage conditions: | in cool, well ventilated area above 5°C. Do not store above 30°C. Keep container tightly closed (S7) |
| Suitable packaging: | Must only be kept in original packaging. |

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

| | |
|--------------------------------|---|
| Respiratory protection: | In case of insufficient ventilation, wear suitable respiratory equipment (S38). |
| Hand protection: | Impervious gloves. (Plastic or Rubber recommended) |
| Eye protection: | Wear approved Safety goggles. |
| Skin protection: | Wear protective overalls. |

EXPOSURE LIMIT VALUES.

| Substance | LTEL/8 hr TWA |
|---------------|-----------------------|
| White Spirit. | 600 mg/m ³ |

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|-----------------------------|--|
| State; | Coloured liquid paste miscible with most organic solvents. |
| Odour: | Smells of solvent |
| Flashpoint: | 40°C |
| Specific Gravity: | 1.13 g/cm ³ |
| Colour: | Various |
| Viscosity: | Not known. |
| Solubility in water: | Insoluble. |
| pH. | Not known. |

Auto ignition: Not known.
Vapour pressure: Not known.

10. STABILITY AND REACTIVITY

The product is stable. In use it may form flammable/explosive vapour - air mixture. It is incompatible with organic peroxides.

11. TOXICOLOGICAL INFORMATION

Vapours or aerosols may cause irritation of eyes, nose and respiratory tract.
Prolonged skin contact will result in defatting of the skin, leading to irritation and in some cases, dermatitis.
Inhalation of solvent vapours may give rise to nausea, headaches and dizziness.

12. ECOLOGICAL INFORMATION

Not readily biodegradable. Marine pollutant.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Disposal must be in accordance with local or national legislation.

N.B. Users attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION



ADR.

UN Number: 1263
Hazard Class: 3
Packing Group: III
Proper Shipping Name: Paint.
Tunnel restriction code: D/E

IMCO.

UN Number: 1263
Hazard Class: 3
Packing Group: III
Proper Shipping Name: Paint
Marine pollutant: Yes.

15. REGULATORY INFORMATION

Label for Supply



Xn Harmful



N. Dangerous for the environment

Symbols.

This formulation has not been tested; it has the following phrases

Risk phrases:

R10: Flammable
R 20/21: Harmful by inhalation and in contact with skin.
R36: Irritating to the eyes.
R38: Irritating to skin.
R43: May cause sensitization by skin contact.
R51/53: Harmful to aquatic organisms, may cause long term adverse effects in the aquatic environment.
R66: Repeated exposure may cause skin dryness and cracking.
R67: vapours may cause drowsiness and dizziness.

Safety phrases:

- S2: Keep out of reach of children.
- S16: Keep away from sources of ignition.
- S21: When using do NOT smoke.
- S23: Do not breathe vapour.
- S25: Avoid contact with eyes .
- S28: Avoid contact with the skin, wash immediately with plenty of soap and water..
- S36/37: Wear suitable protective clothing and gloves
- S41: In case of fire or explosion do not breathe fumes.
- S51: Use only in well ventilated areas.

16. OTHER INFORMATION

DISCLAIMER

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication. However no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such materials used in combination with any other materials or in any other process. It is the users responsibility to satisfy themselves as to the application of the information and/or the recommendations given for their own use.