

MATERIAL SAFETY DATA SHEET



FLOOR PAINT

Issue: 2. Issue Date: 29/11/2007.

Page 1 of 4

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY

Product Name. Floor Paint G/R

Supplier. KINGFISHER BUILDING PRODUCTS Ltd.
COOPER LANE.
BARDSEA BUSINESS PARK
ULVERSTON
CUMBRIA.
LA12. 9RA.

Telephone: 01229 869100
Fax: 01229 869101
Emergency: As Above

2. COMPOSITION / INFORMATION ON INGREDIENTS.

Ingredient Name.	CAS.No	Einecs	Content	Health (Class)	Risk (R No.)
White Spirit	64742-82-1	265-185-4.	1-5%	N.	R10, R51/53. R65
Cobalt Carboxylate	13586-82-8	237-015-9	<1%	Xn, Xi, Sens, Xn,	R22,38,43,51/53,65
White Spirit	64742-48-9	265-150-3	30-50%	Xn, Xi	R10,65,66.

3. HAZARDS IDENTIFICATION

FIRE: - Flammable. R10

ENVIRONMENT: - Harmful to aquatic organisms, may cause long term adverse effects in the aquatic environment

Inhalation: - May be a feeling of tightness in the chest with shortness of breath.

Eye Contact:- May cause irritation and pain.

Skin Contact: - May cause irritation and redness at site of contact.

Ingestion: - May be soreness and redness of the mouth and throat.

4. FIRST AID MEASURES.

Inhalation:- Remove to the fresh air. If breathing has stopped, administer artificial respiration. Seek medical attention.

Eye Contact: - Remove contact lens if necessary. Irrigate with copious amounts of clean, fresh water for at least 15 minutes keeping eyelids open. Seek medical help.

Skin Contact: - Remove contaminated clothing. Wash skin thoroughly with soap and water. Consult a Doctor

Ingestion:- Wash out mouth with water. Seek immediate medical help.

MATERIAL SAFETY DATA SHEET (Continued)

FLOOR PAINT

Issue No: 2. Issue Date: 29/11/2007 Page 2 of 4

5. FIRE FIGHTING MEASURES.

- Extinguishing Media:** - Suitable extinguishing media for the surrounding fire should be used. Use Water spray/mist to cool containers
- Protective Measures in Fire:** - Wear self contained breathing apparatus. Wear protective clothing to protect skin and eyes.
- Exposure Hazards :-** In combustion emits toxic fume.

6. ACCIDENTAL RELEASE MEASURES.

- Personal Protection during Spill:** - Refer to Section 8 for PPE detail.. turn leaking containers leak side up to prevent spillage.
- Precautions to Protect Environment:** - Exclude sources of ignition and non essential personnel. Do not allow entry to drains or water courses
- Spillage Clean Up Methods:** - Contain spillage with non combustible absorbent materials. i.e. sand, earth etc. Place in closable labelled containers for disposal.
If product enters drains, inform the local water company.

7. HANDLING AND STORAGE.

- Usage Precautions:-** Avoid the formation or spread of mists in the air. Ensure sufficient ventilation of the area.
- Storage Criteria:-** Store between 5°C and 25°C in a dry environment. Keep away from sources of ignition, heat and direct sunlight. Keep containers tightly closed.
Stores area should be a No Smoking area.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION.

- Engineerig Measures:-** Ensure there is sufficient ventilation of the area.
- Personal Protective Equipment:** - Self contained breathing apparatus must be available in case of emergency. Gas/vapour filter type A : Organic vapours(EN141).
Wear Gloves, goggles and protective clothing.

MATERIAL SAFETY DATA SHEET (Continued)

FLOOR PAINT

Issue No: 2. Issue Date: 29/11/2007

Page 3 of 4

9. PHYSICAL AND CHEMICAL PROPERTIES.

Appearance: - Viscous Liquid. **Colour:-** Grey.
Odour: - Characteristic. **Viscosity:** - Viscous
Solubility in Water: - Not miscible. **Flash Point:** - 40°C

Soluble in most organic solvents.

10. STABILITY AND REACTIVITY

Stability: Stable under recommended storage and handling conditions.

Materials to Avoid: Keep away from oxidising agents and strongly alkaline and acidic materials to prevent the possibility of exothermic reaction.

Conditions to avoid: High temperatures and sources of ignition.

11. TOXICOLOGICAL INFORMATION.

Refer to Section 4 for routes of exposure.

12. ECOLOGICAL INFORMATION.

Environmental Hazards. Toxic to aquatic organisms.

Mobility :- Readily absorbed into soil

Degradability: . Only slightly biodegradable

13. DISPOSAL CONSIDERATIONS

Disposal Methods: Waste product and containers are controlled wastes and should be disposed of in accordance with regulations made under The Control of Pollution Act and The Environmental Protection Act.

MATERIAL SAFETY DATA SHEET (Continued)

FLOOR PAINT

Issue No: 2. Issue Date: 29/11/2007

Page 4 of 4

14. TRANSPORT INFORMATION

Label for Conveyance. Paint.

Hazard Class.	3	Trans. Cat.	III
UN No.	1263	Marine Pollutant.	
Shipping Name	Paint	Hazard ID no.	30

15. REGULATORY INFORMATION

Label for Supply: No significant hazard

Risk Phrases :

- R10 Flammable
- R43 may cause sensitisation by skin contact.
- R51/53. Toxic to aquatic organisms, may cause long term adverse effects to the aquatic environment.
- R65 harmful may cause lung damage if swallowed.
- R66. Repeated exposure may cause skin dryness or cracking

Safety Phrases :

- S23. Do not breathe vapour spray.
- S24. Avoid contact with skin.
- S29/35. Do not empty into drains; dispose of this material and its container in a safe way.
- S51. Use only in well ventilated areas.
- S61. Avoid release to the environment.

16. OTHER INFORMATION

User Notes :

THE INFORMATION GIVEN IN THIS DATA SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS TO THE BEST OF THE COMPANY,S KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS OF THE DATE INDICATED. HOWEVER NO WARRANTY, GUARANTEE OR REPRESENTATION IS MADE AS TO ITS ACCURACY,RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY THEMSELVES AS TO THE SUITABILITY AND APPLICATION OF SUCH INFORMATION FOR THEIR OWN USE