

MATERIAL SAFETY DATA SHEET (Continued)

SX Polysulphide Sealant

Issue: 2.

Issue Date: 07/12/2004.

Page 1 of 4

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY

Product Name. SX Polysulphide Sealant
Use of the product. Sealant for the building industry.

Supplier. KINGFISHER BUILDING PRODUCTS Ltd.
COOPER LANE.
BARDSEA BUSINESS PARK
ULVERSTON
CUMBRIA.
LA12 9RA.

Telephone: 01229 869100
Fax: 01229 869101
Emergency: As Above

2. COMPOSITION / INFORMATION ON INGREDIENTS.

Chemical characterization : Polysulphide polymer, with fillers, plasticiser and auxiliaries, and barium oxide.

Ingredient Name.	CAS.No	Einecs	Content	Health (Class)
2-MERCAPTOETHANOL	200-464-6	60-24-2	<1%	T:R23/24/25
CALCIUM OXIDE	215-138-9	1305-78-8	1-5%	Xi, R37/38, R41
LIQUID POLYSULPHIDE POLYMER With thiol end groups (MW>1800)		68611-50-7	10-30%	R52/53

The Full Text for all R-Phrases are Displayed in section 16.

COMPOSITION COMMENTS

Polysulphide polymer, with fillers, plasticiser and auxiliaries.

3. HAZARDS IDENTIFICATION

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION : R52/53

Human Health : The product contains a small amount of sensitising substance which may provoke an allergic reaction among sensitive individuals in contact with skin

PRODUCT SAFETY DATA SHEET (Continued)

SX Polysulphide Sealant

4. FIRST AID MEASURES.

General Information :	In all cases of doubt, or if symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Eyes :	Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.
Ingestion :	Immediately rinse mouth with plenty of water. If person becomes uncomfortable or if ingested in large amounts (50-100ml for an adult person) Take to hospital along with these instructions.
Inhalation :	Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

5. FIRE FIGHTING MEASURES.

Extinguishing media : Water spray, Dry powder, Foam or CO2.

6. ACCIDENTAL RELEASE MEASURES.

Personal Precautions :	Wear appropriate protective clothing.
Environmental Precautions :	Avoid discharge into drains, water courses or onto the ground
Spill Clean up Methods :	Shovel into dry containers. Cover and move the containers. Flush the area with water. Wash thoroughly after dealing with the spillage.

7. HANDLING AND STORAGE.

Usage precautions :	Avoid spilling, skin and eye contact. Observe good industrial hygiene practices
Storage precautions :	Store in tightly closed original container in a dry and cool place.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Engineering Measures :	Well-ventilated area
Hand Protection :	Use suitable protective gloves if risk of skin contact
Eye Protection :	Wear approved safety goggles
Hygiene Measures :	DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

MATERIAL SAFETY DATA SHEET (Continued)

SX Polysulphide Sealant

9. PHYSICAL AND CHEMICAL PROPERTIES.

Appearance :	Uncured - paste. Cured – rubber.
Colour :	Misc. colours
Odour :	Mercaptan
Solubility :	Insoluble in water
Relative Density :	1.69 – 1.72 @ 20°C
Flash Point (°C) :	>100
Viscosity :	7,000 – 14,000 Ps @ 20°C
Auto Ignition Temperature (°C) :	430

10. STABILITY AND REACTIVITY

Stability :	Stable under normal temperature conditions and recommended use.
Conditions to avoid :	Avoid excessive heat for prolonged periods of time.
Materials to avoid :	Strong oxidising substances.
Hazardous decomposition products :	No specific hazardous decomposition products noted.

11. TOXICOLOGICAL INFORMATION.

Toxic Dose 1 –LD 50 :	Not determined
Inhalation :	No specific health warnings noted
Ingestion :	No harmful effects expected in amounts likely to be ingested by accident
Skin Contact :	Prolonged and frequent contact may cause redness and irritation. The product contains a small amount of sensitising substance which may provoke an allergic reaction among sensitive individuals after repeated contact.
Eye Contact :	May cause irritation to eyes.
Health Warnings :	Product contains: alkaline material which can cause skin irritation and eye damage.

12. ECOLOGICAL INFORMATION.

Ecotoxicity :	The product contains a substance which is harmful to aquatic organisms and which may cause long term adverse effects in the aquatic environment.
LC 50, 96 Hrs FISH mg/l :	Not determined
Mobility :	The product is insoluble in water.
Bioaccumulation :	No data available on bioaccumulation.
Degradability :	Poorly biodegradable

13. DISPOSAL CONSIDERATIONS

Disposal Methods: Disposal of material and packaging should be by incineration in accordance with local regulations.

14. TRANSPORT INFORMATION

No regulations apply for the transportation of this material.
Not classified as hazardous for road, rail, sea or air transport.

PRODUCT SAFETY DATA SHEET (Continued)

SX Polysulphide Sealant

15. REGULATORY INFORMATION

- Risk phrases :** R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- Safety phrases :** S60 This material and its container must be disposed of as hazardous waste
P-14 Contains 3-GLYCIDOXYPROPYLTRIMETHOXYSILANE. May produce an allergic reaction.
- Statutory instruments :** Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.
- Guidance notes :** Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

16. OTHER INFORMATION

RISK PHRASES IN FULL

- R23/24/25 :** Toxic by inhalation, in contact with skin and if swallowed.
- R37/38 :** Irritating to respiratory system and skin
- R41 :** Risk of serious damage to eyes
- R52/53 :** Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

THE INFORMATION GIVEN IN THIS DATA SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS TO THE BEST OF THE COMPANY'S KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS OF THE DATE INDICATED. HOWEVER NO WARRANTY, GUARANTEE OR REPRESENTATION IS MADE AS TO ITS ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY THEMSELVES AS TO THE SUITABILITY OF SUCH INFORMATION FOR THEIR OWN USE